



Antifouling Compatibility table

New Product to be applied

Seajet 033 Shogun Seajet 034 Emperor Seajet 037 Coastal Seajet Speed
 Seajet 031 Samurai Seajet 039 Platinum Seajet 030 Warrior Foul Release

Existing Product

Existing Product	Seajet 038 Alusafe	Seajet 033 Shogun	Seajet 034 Emperor	Seajet 037 Coastal	Seajet Speed Foul Release
Seajet 033 / Seajet 038 / Seajet 031	0	0	0	0	2
Seajet 034 Emperor/ Seajet 039 Platinum	0	0	0	0	2
Seajet 037 Coastal / Seajet 030 Warrior	0	0	0	0	2
Seajet Speed	2	2	2	2	0
Optima	0	0	0	0	2
Micron Extra / Micron CSC	0	0	0	0	2
Cruiser Premium/ Cruiser Uno	0	0	0	0	2
Boatguard	1	1	0	0	2
Trilux	1	1	0	0	2
Waterways	1	1	0	0	2
Interspeed Ultra	1	1	0	0	2
VC Offshore	1	1	1	1	2
VC17M	3	3	3	3	3
Micron 55 / 66	0	0	0	0	2
Ocean Performer	0	0	0	0	2
Tiger Extra / Titan Ultra	0	0	0	0	2
Cruising Performer / Tiger Cruising	0	0	0	0	2
Hard Racing Ultra	3	3	1	1	3
Lynx	1	1	1	1	2
Broads	1	1	0	0	2
Waterline	2	2	2	2	3
Mille	0	0	0	0	2
Hard Racing	1	1	1	1	2
Non Stop	0	0	0	0	2
Super Tropic	1	1	0	0	2
Marenostrom	1	1	0	0	2
Nautix A2	0	0	0	0	2
Nautix A3	1	1	0	0	2
Nautix A3 T. Speed	3	3	3	3	3
Nautix A4	1	1	1	1	2
Nautix A4 T. Speed	3	3	3	3	3
Gold label - Awlgrip	1	1	1	1	2
XM C2000 Eroding	1	1	0	0	2
XM HS3000 Eroding	1	1	0	0	2
XM P4000 Hard	2	2	0	0	2
Plastimo 1.1	1	1	0	0	2
Plastimo 1.2	1	1	1	1	2
Plastimo 1.3	3	3	3	3	3
Compass Antifouling (all types)	1	1	1	1	2
Neymeyer / van. Höveling	1	1	1	1	2
Teflon Antifouling	3	3	3	3	3
Hard Antifouling	1	1	1	1	2
Soft Antifouling	2	2	2	2	3
Unknown Antifouling	2	2	2	2	3
Tin-Based SPC Antifouling	0	0	0	0	2

0 - Apply antifouling after removing slime or fouling with high pressure fresh water, remove loose antifouling and spot repair with the recommended primer.

1 - As above but light wet-sanding of the existing antifouling is required, then rewash before painting

2 - As above but apply a barrier coat of Seajet 011 Underwater Primer (or Seajet Speed Undercoat) before applying the antifouling.

3 - Remove the existing antifouling and apply the recommended primer system before applying antifouling

Don't take any risks! Remove existing antifouling in poor condition.